

# **TECEone Shower WC - Cold Feed**

Article Number: 9700201

## **Description:**

The TECEone wall hung shower WC pan has been specially developed to fit and function with all Tece frames and others produced by all major manufacturers. A rimless design, built to work with all frame sizes and with flush volumes of 4.5 or 6 litres making it the perfect product for the eco-conscious. No electrical supply is required. **E&OE** 

## **Applications:**

TECEone wall hung shower WC pans are designed to fit onto WC frames, fitted into en-suites, cloakrooms and other bathroom projects where wall hung shower WC pans are required. Suitable for:

- Small and large bathrooms, where space is at a premium, while ease of cleaning & sleek design is a priority.
- All major manufacturers WC frames with 180mm pan fixing centres.
- Installations where cold-water feeds are available, but not electric supply.
- Premium design-led bathroom installations, where aesthetic considerations require sleek product solutions.
- Can be fitted for comfort height installations providing the frame can be adjusted to suit required height.
- Can be used with 'grey' rainwater recycling systems when adequately filtered.

# Product characteristics and key features:


- Increase or decrease water pressure on shower nozzle up to 5.6 lpm.
- Type AD backflow prevention device on shower function, protecting against Cat 5 contaminants.
- Self-cleaning shower nozzle that is also replaceable.
- Minimum feed pressure for shower function of 1.5 bar (max. 10 bar).
- Manufactured in accordance with EN997.
- Suitable for TECE WC frame cistern frame ranges.
- Hygienic ceramic design with fewer corners, edges, or joins.
- 4.5 and 6 litre flush volume compatible.
- Braided stainless-steel cold-water feed pipe.
- Integral concealed pan hanging locations.
- Hard Mounted seat locations to suit TECE seat and lid (seats sold separately see pricelist).





### **Technical Data:**

SIZE, Height x Width x Depth: PRESSURE, Minimum Shower Feed: PRESSURE, Rotary Control: 400 x 358 x 540mm 1.5 bar (Max. 10 bar)

Increase or decrease water pressure on shower nozzle using rotary control up to 5.6 lpm







# Specification clause:

The TECEone rimless ceramic wall-hung shower WC pan, compatible with all major WC frames (180mm pan fixing centres), features a hygienic design for 4.5 or 6-litre flush volumes, rotary controls for water pressure up to 5.6 lpm, pre-assembled seat fastenings, a Type AD backflow prevention device, a self-cleaning nozzle, and is certified to EN997 standards with a minimum water pressure of 1.5 bar and a maximum of 10 bar.

### Contents:

Supplied in Single BOX (N.B. order control plates separately).

- TECEone rimless wall hung WC pan .
- Pre-assembled fastening locations for toilet seat.
- Thermostatic and water pressure controls pre-fitted.
- Self-cleaning shower nozzle pre-fitted.
- Installation guides.

### Please order separately:

- TECE toilet seat with CLASSIC lid (Item No. 9700600).
- TECE toilet seat with SLIM lid (Item No. 9700603).
- Shower Toilet/Seat Connection Set (Refer to Product List).


# Packaging:

- Single items, Heavy Duty Box: Size (W x H x D): 425 x 460 x 590mm.
- Disposal: According to local Bylaws.
- Ready to install, factory sealed.

# **Installation Instructions:**

See separate sheet: Included in package.

### **Spare Parts:**



No.	Article No
1	9820356
2	9820357
3	9820362
4	9820469
7	9820471
8	9820364
9	9820403
10	9820404
11	9820405
12	9820406
13	9820363
14	9820422
15	9820351
16	9820484
17	9820585
18	9820586

# Spare Parts Concealed mounting Knurled nut (2x) for concealed mounting Control knob for water volume, plastic white Ceramic cartridge including EN 1717 safeguard Reinforced hoses Rosette, white Shower nozzle cap (3 x) "standard" 75', white Shower nozzle cap (3x) "standard" 90' white Shower nozzle cap (3x) "small" 90' White Shower nozzle cap (3x) "small" 90' White TECE shower arm complete set, white, Removal tool shower arm Sound insulation tape Seal for flush pipe connection O-ring for shower arm spring retainer O-ring for safety device EN 1717

### E&OE

We reserve the right to alter and amend specifications without prior notice. This is not a specification document and does not guarantee performance.

### SPARES AND REPAIRS

We guarantee that spare parts will be available for all cisterns, frames and pans for at least 25 years after cease of manufacture.

